

Product Highlights

Efficient and environmentally friendly

- Higher work efficiency
- Environmental protection, zero emissions

Reduced maintenance costs

- Exclusive open chassis design reduces daily maintenance costs
- Rapid, convenient transportation with two-way forklift slot
- Lower cost of ownership with highly versatile parts and components

More reliable performance

- New wide scissor design, for a more stable working-at-height experience
- Bumper rail and indented sliding groove designed for anti-scratch

Standard features		
■ Maintenance-free battery	■ Automatic braking system	■ Drive at full height
■ Proportional control	■ Emergency lowering system	■ Forklift pocket and lifting eyes
■ Bumper rail	■ Emergency stop at both platform and ground controls	■ Electrophoresic paint technology
■ 4×2 drive	■ Fault diagnosis system	■ Foldable guardrail
■ Non-marking tyres	■ Tilt protection	■ Overload sensing system
■ Integrated hand shield	■ Automatic pothole guard	
Optional features		
■ Overhead anti-collision device	■ Headlight	■ RCBO
■ AC power to platform		



SINOBOOM

Sinoboom Intelligent Equipment Co Ltd

📍 No.128 East Jinzhou Av., Ningxiang Hi-Tech Industry Park, Changsha, Hunan, China, 410600

🌐 www.sinoboom.com

✉ sales@sinoboom.com

Electric Series Scissor Lifts

0808E (2732E)

Complies with ISO/CE/ANSI/AS/CU-TR/KCS standards

Model		0808E (2732E)	
Dimensions		Metric	
Max Working		10.1m	
A Max Platform		8.1m	26'7"
B Max Horizontal		0.9m	3'
C Length-		2.46m	8'
D Width-Stowed		0.83m	
Height-stowed	Rail Folded	1.96m	
	E Rail Unfolded	2.36m	
F Wheelbase		1.88m	
Ground Clearance (Pothole Guard Stowed)		0.1m	4"
Ground Clearance (Pothole Guard)		25mm	
Platform		2.30m×0.8m×1.1 (7'6.5"×2'7.5"×3'7")	
Performance			

Platform Allowable Occupants (Indoor/Outdoor)	2 persons/-	
Platform Capacity	250kg	551lbs
Drive Speed-Stowed	4km/h	2.5mph
Drive Speed-Raised	0.8km/h	0.5mph
Elevation Time(Unloaded)	30s~35s	
Descent Time(Unloaded)	34s~39s	
Gradeability	25%	
Turning Radius(Inside/Outside)	0/2.1m	
Tilt Rating(Front to Back/Side to Side)	3°/1.5°	
Tyres-solid	380×125mm(15×5")	

Power	
Batteries	6V×4/225Ah
Power Source	24V DC
Drive Mode	Motor, front-wheel 100~240V
Charger Input	AC
Charger Output	30A
Hydraulic System Capacity	15L 3.3gal

Weight	
Weight	2,265kg 4,994lbs
	Indoor only

Standards Compliance

